

**Certification
Issued Under the Authority of the
Federal Communications Commission
By:**

**DERYCOM CERTIFICATION SERVICES,
INC.
1100 Falcon Avenue
Glencoe, MN 55336**

**Date of Grant: 03/23/2026
Application Dated: 03/23/2026**

**Shanghai Yuge information technology Co., Ltd.
Room 204-1, No. 6, Lane 88, Shengrong Road
China (Shanghai) pilot Free Trade Zone,
Shanghai,
China**

Attention: Guixia Wu , Manager

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: 2BG5S-CLM920-JC3
Name of Grantee: Shanghai Yuge information technology Co., Ltd.
Equipment Class: PCS Licensed Transmitter
Notes: 4G LTE Wireless Communication Module
Modular Type: Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	24E	1852.4 - 1907.6	0.455	0.01 PM	4M15F9W
	27	1712.4 - 1752.6	0.522	0.01 PM	4M15F9W
	22H	826.4 - 846.6	0.3	0.01 PM	4M15F9W
	24E	1860.0 - 1900.0	0.402	0.01 PM	17M9G7D
	24E	1860.0 - 1900.0	0.348	0.01 PM	17M9W7D
	24E	1850.7 - 1909.3	0.438	0.01 PM	1M10G7D
	24E	1857.5 - 1902.5	0.356	0.01 PM	13M4W7D
	27	1720.0 - 1745.0	0.428	0.01 PM	17M9G7D
	27	1720.0 - 1745.0	0.374	0.01 PM	17M9W7D
	27	1710.7 - 1754.3	0.48	0.01 PM	1M09G7D
	27	1710.7 - 1754.3	0.394	0.01 PM	1M10W7D
	22H	829.0 - 844.0	0.267	0.01 PM	8M95G7D
	22H	829.0 - 844.0	0.213	0.01 PM	8M94W7D
	22H	826.5 - 846.5	0.279	0.01 PM	4M50G7D
	22H	826.5 - 846.5	0.228	0.01 PM	4M50W7D
	27	2510.0 - 2560.0	0.332	0.01 PM	17M9G7D
	27	2510.0 - 2560.0	0.291	0.01 PM	17M9W7D
	27	2502.5 - 2567.5	0.352	0.01 PM	4M50G7D
	27	2502.5 - 2567.5	0.294	0.01 PM	4M50W7D

27	704.0 - 711.0	0.16	0.01 PM	8M94G7D
27	704.0 - 711.0	0.132	0.01 PM	8M94W7D
27	699.7 - 715.3	0.176	0.01 PM	1M09G7D
27	699.7 - 715.3	0.144	0.01 PM	1M10W7D
27	782.0 - 782.0	0.152	0.01 PM	8M93G7D
27	782.0 - 782.0	0.116	0.01 PM	8M93W7D
27	779.5 - 784.5	0.168	0.01 PM	4M50G7D
27	779.5 - 784.5	0.147	0.01 PM	4M50W7D
27	709.0 - 711.0	0.147	0.01 PM	8M95G7D
27	709.0 - 711.0	0.124	0.01 PM	8M95W7D
27	706.5 - 713.5	0.155	0.01 PM	4M50G7D
27	706.5 - 713.5	0.136	0.01 PM	4M50W7D
27	2580.0 - 2610.0	0.376	0.01 PM	18M0G7D
27	2580.0 - 2610.0	0.32	0.01 PM	17M9W7D
27	2506.0 - 2680.0	0.376	0.01 PM	18M0G7D
27	2506.0 - 2680.0	0.314	0.01 PM	17M9W7D
27	2503.5 - 2682.5	0.378	0.01 PM	13M5G7D
27	2503.5 - 2682.5	0.334	0.01 PM	13M5W7D
27	1720.0 - 1770.0	0.43	0.01 PM	17M9G7D
27	1720.0 - 1770.0	0.381	0.01 PM	17M9W7D
27	1710.7 - 1779.3	0.473	0.01 PM	1M09G7D
27	1712.5 - 1777.5	0.393	0.01 PM	4M51W7D

Single Modular Approval. Power output listed is ERP for frequencies below 1GHz and EIRP for frequencies above 1GHz. OEM integrators and end-users must be provided with transmitter operation conditions for satisfying RF exposure compliance. Only the antenna tested with the device or similar antennas with equal or lesser gain may be used with this transmitter. The antenna used with this transmitter must be installed to provide a minimum separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter, except in accordance with FCC multi-transmitter product procedures. End-users must be provided with operating procedures for satisfying RF exposure compliance. This device also contains functions that are not operational in U.S. Territories. This filing is only applicable for US operations.